



WHEELCHOCK SAFETY SYSTEM

MEETS MANDATORY GOVERNMENT REGULATIONS

OSHA. Regulation 1910.178 (k)(1)

The brakes of highway trucks shall be set & wheel chocks placed under the rear wheels to prevent the trucks from rolling while they are boarded with powered industrial trucks.

Ontario Health & Safety Act.

R.R.O. 1990, Reg. 851, S 57. A vehicle left unattended shall be immobilized & secured against accidental movement.



LAMINATED WHEEL CHOCK

Recycled rubber laminated & fastened under high pressure galvanized steel sides to ensure long life



"ICE GRIP" WHEEL CHOCK

"Tooth" like bottom assures reliable grip on icy / slippery surfaces powder coated safety yellow for high visibility



RUBBER WHEEL CHOCK

Recycled rubber material provides basic protection against trailer movement



CHOCK HOLDER BRACKET

Primed and painted holder allows for storage of chock off the ground preventing snowplow from clearing chocks by accident



GALVANIZED WELDED CHAIN

15 Feet provided to secure chock to building wall

"Professional Installation & 24 Hour Service"

Phone: 416-676-1117, 888 676 1117

3425 Laird Rd. Mississauga, ON L5L 5R8



For more information visit us at www.prodoor.ca